

Section 1

**LOW VOLTAGE 2V TO 9V
AC TO DC SINGLE OUTPUT**

Pioneer’s low voltage high current series provides a wide range of single output PFC Models. The high current models come in the traditional 5”x 5” package configured as hot plug or non-plug. The premium Quality, high performance, high current switchers are rugged with high reliability. These units are featured with 20ms hold up time for the output, internal forced air-cooling and built-in protection from electrical overloads.

A single module provides continuous full power over operating temperatures of 0°C to +50°C, from a Single Phase or Three Phase AC input line ranging from 90 to 264VAC.

Product Matrix

MODEL	PM3346	PM3347	PM3348	PM3399	PM33910	PM33911
MAX POWER	1000W	1200W	1500W	2000W	2500W	3000W
OUTPUT Vout	lout	lout	lout	lout	lout	lout
2V	200A	240A	300A	400A	500A	600A
3.3V	200A	240A	300A	400A	500A	600A
5V	200A	240A	300A	400A	500A	600A
6V	167A	200A	250A	333A	416A	500A
9V	111A	133A	167A	222A	277A	333A
Non-Plug	5”	5”	11.25”	5” x 6.25” x 13”	5” x 6.25” x 13”	5” x 8” x 13”
Hot Plug	5”	5”	14”	5” x 6.25” x 15”	5” x 6.25” x 15”	5” x 8” x 15”
AC INPUT	90V	to	264V	180V	to	264V

- Notes:
- All Models are available with wide input range 90 to 264VAC (option –6) or high input 180 to 264VAC (option –5)
 - All Models are available in AC Input, 1P or 3P.
 - Input Current formula: $1\phi \text{ lin} = P_{out}/(V_{in} \times \text{Efficiency} \times 0.99\text{PFC})$
 $3\phi \text{ lin} = P_{out}/(V_{in} \times \text{Efficiency} \times 0.95\text{PFC} \times \sqrt{3})$

Features:

- ◆ Power Factor Correction
- ◆ 0°C to +50°C at Full Load
- ◆ De-rated @ 70°C
- ◆ Outputs Fully Floating
- ◆ Over Current Protection
- ◆ Over Voltage Protection
- ◆ Remote Sense
- ◆ Over Temperature Protection
- ◆ Internal Forced Air Cooling

Options:

- ◆ (-128L) DC OK with LED indicator
- ◆ (-1CL) AC Fail with LED indicator
- ◆ (-2T) Unit enable/disable
- ◆ (-5LO) ±10% Output voltage swing
- ◆ (-6B) Single wire current sharing
- ◆ (-6D) Slope/Droop current sharing
- ◆ (-20C) Isolation diodes
- ◆ (-25) Constant current limit
- ◆ (-33) Current monitor

Note: Refer to Section 26 for list of all standard options

SPECIFICATION

Inputs

RANGE: 90 to 264 VAC, 1 ϕ or 3 ϕ .
FREQUENCY: 47 to 63 Hz. 400Hz also available as an option
POWER FACTOR:
 0.99 @ Full Load for 1 ϕ
 0.95 @ Full Load for 3 ϕ
INRUSH CURRENT: < 25A when averaged over 1/2 cycle.
HARMONIC CURRENT: < 5% for 1 ϕ only
HOLD UP TIME: At least 20msec from loss of input to loss of regulation.

Environmental

AUDIBLE NOISE: 63dBA/70dbA max at 1 meter
TEMPERATURE: Operating: 0°C to +50°C at full load. Storage: -55°C to +85°C.
HUMIDITY: 20% to 95% non-condensing.
ALTITUDE: Operating: 5,000 feet. De-rates to 75% at 15,000 feet. Non-Operating: To 30,000 feet.
VIBRATION: Operating: From 5 to 27 Hz, 0.02 in double amplitude; from 27 Hz to 500 Hz, 0.75G, 3 Axes, 3 min per octave sweep, dwell 15 min at resonance. Non-operating: From 5 to 17 Hz, 0.10 in double amplitude, from 17 to 500Hz, 1.5G peak; 3 axes, 5 min per octave sweep; dwell 15 min at resonance.
SHOCK: Operating: 5G, half sine, 11msec, 3 axes. Non-Operating: 15G, half sine, 11msec, 3 axes.
COOLING: Forced air, internal fan. Airflow exits at connector end

Output

ADJUSTMENT RANGE: $\pm 10\%$ of nominal output voltage.
POLARITY: Output is isolated. It may be referenced plus/minus as required.
REMOTE SENSE: Compensates for up to 0.5V total loop drop, in the output line.
STATIC REGULATION:
 Line: $\pm 0.25\%$ over full line range.
 Load: $\pm 0.25\%$ zero load to full load.
VOLTAGE STABILITY: $\pm 0.1\%$ for 24 hour period after 30 minute warm up.
TEMP COEFFICIENT: $\pm 0.02\%/^{\circ}\text{C}$ from 0°C to +50°C.
P-P RIPPLE AND NOISE: 1% (20Hz to 50MHz Bandwidth).
MINIMUM LOAD: Not Required.
TURN ON DELAY: 1sec max from application of AC line.

Internal Protection

OVER VOLTAGE PROTECTION: 125% $\pm 5\%$ of nominal. OVP shutdown is latched until the input line is removed for 30 seconds and then reapplied. OVP sensing is done at the output terminals.
OVERCURRENT PROTECTION: Current Limit Point: 110% to 120% of full load.
SHORT CIRCUIT CURRENT: Fold back type to 40%-80% of full rated current. Unit will recover when overload is removed.
REVERSE VOLTAGE PROTECTION: Protected to rated load with the fan running.
OVERTEMPERATURE PROTECTION: The unit automatically shuts down in the event of an over temperature condition. After cool down, power must be recycled to restart unit. Optionally, non-latchable protection is also available.

Safety

SAFETY: UL1950, CSA22.2 No 950 and TUV to EN60950. CE Mark (LVD)
EMI: Conducted & Radiated: EN55022 Level A
 CE Certification is Optional



5" x 5" x 11.25"
 Up to 1500W
 DC Bus Bars
 AC Terminal Block
 Option Connector DB25



5" x 5" x 14"
 Up to 1500W
 Elcon Top Drawer
 Hot Plug Connector



5" x 8" x 13"
 Up to 3000W
 DC Parallel Bus Bars
 AC Terminal Block
 Option Connector DB25