

Section 17

DC TO DC HIGH VOLTAGE 70V TO 300V HIGH POWER SERIES

Pioneer introduces a new breed of High Efficiency, High Voltage and High Power DC to DC Series that provide full output power with DC Input ranging from 90VDC to 750VDC. Designed to support both standalone and parallel configurations, these models are configured in standard Non-Plug and Hot Plug I/O interfaces. The Premium Quality front ends are rugged, reliable, designed for high performance and come in the traditional 5" x 5" package. With power density up to 25.8 watts/in³, these units are featured with internal forced air-cooling and built-in protection from electrical over-loads.

A single module provides continuous full power over operating temperatures of 0°C to +50°C.

Product Matrix

MODEL	PM3336	PM3337	PM3338	PM3339	PM33311	PM3339	PM33310	PM33315	PM36316	PM36318	PM36319
MAX POWER	1000W	1200W	1500W	2000W	3000W	2000W	2500W	5000W	6000W	8100W	10000W
Vout	lout	lout	lout	lout	lout	lout	lout	lout	lout	lout	lout
70V	14A	17A	21A	29A	43A	29A	36A	71A	86A	116A	143A
90V	11A	13A	17A	22A	33A	22A	17A	56A	67A	90A	111A
100V	10A	12A	15A	20A	30A	20A	25A	50A	60A	80A	100A
150V	8.3A	8A	10A	13A	20A	13A	17A	34A	40A	53A	67A
200V	5A	6A	8A	10A	15A	10A	13A	25A	30A	40A	50A
250V	4A	5A	6A	8A	12A	8A	10A	20A	24A	32A	40A
300V	3A	4A	5A	7A	10A	7A	8A	17A	20A	27A	33A
Non-Plug	5"	5"	11.25"	5" 5"	11.25"	5" 5"	15.5"	5"	5"	15.5"	
Hot Plug	5"	5"	11.50"	5" 5"	11.5"	5" 5"	17"	5"	5"	17"	
DC Input	90V	to	350V	180V	to	350V	90V	to	350V	180V	to 350V or 400V to 750VDC

Notes: 1. All Models are available with wide DC input range 90 to 350V or high input 180 to 350VDC
 2. Models with output ≥ 4000W are also available with DC Input range 400 to 750VDC

Features:

- ◆ Power Factor Correction
- ◆ 0°C to +50°C at Full Load
- ◆ De-rated @ 70°C
- ◆ Standard 5" x 5" Case
- ◆ Outputs Fully Floating
- ◆ Over Current Protection
- ◆ Over Voltage Protection
- ◆ Remote Sense
- ◆ Over Temperature Protection
- ◆ Internal Forced Air Cooling

Options:

- ◆ (-128L) DC OK with LED indicator
- ◆ (-1UL) DC Input Monitor with LED indicator
- ◆ (-2T) Unit enable/disable
- ◆ (-5LO) ±10% Output voltage adjust
- ◆ (-6B) Single wire current sharing
- ◆ (-6D) Slope/Droop current sharing
- ◆ (-20C) Isolation diodes
- ◆ (-25) Constant current limit
- ◆ (-33) Current monitor

Note: Refer to Section 26 for list of all standard options

SPECIFICATION

Inputs

RANGE:

Up to 1500W - 90 to 350VDC
 > 1500W - 180 to 350VDC

INRUSH CURRENT: < 25A/40A averaged over 10msec.

REVERSE POLARITY PROTECTION: Reverse voltage within rating will not damage power supply.

INPUT FUSING: External Fuse Required

HOLD UP TIME: At least 20msec from loss of input to loss of regulation.

Environmental

AUDIBLE NOISE: 63dB/70dB max at 1 meter

TEMPERATURE: Operating: 0°C to +50°C at full load.
 Storage: -55°C to +85°C.

HUMIDITY: 20% to 95% non-condensing.

ALTITUDE: Operating: 5,000 feet. De-rates to 70% at 15,000 feet. Non-Operating: To 30,000 feet.

VIBRATION: Operating: From 5 to 27 Hz, 0.02 in double amplitude; from 27 Hz to 500 Hz, 0.75G, 3 Axes, 3 min per octave sweep, dwell 15 min at resonance. Non-operating: From 5 to 17 Hz, 0.10 in double amplitude, from 17 to 500Hz, 1.5G peak; 3 axes, 5 min per octave sweep; dwell 15 min at resonance.

SHOCK: Operating: 5G, half sine, 11msec, 3 axes. Non-Operating: 15G, half sine, 11msec, 3 axes.

COOLING: Forced air, internal fan. Airflow exits at connector end.

Output

ADJUSTMENT RANGE: +5% to -10% of nominal output voltage.

POLARITY: Output is isolated. It may be referenced plus/minus as required.

REMOTE SENSE: Compensates for up to 0.5V total loop drop, in the output line.

STATIC REGULATION:

Line: ±0.25% over full line range.

Load: ±0.25% zero load to full load.

VOLTAGE STABILITY: ±0.1% for 24 hour period after 30 minute warm up.

TEMP COEFFICIENT: ±0.02%/°C from 0°C to +50°C.

P-P RIPPLE AND NOISE:

1% (20Hz to 50MHz Bandwidth).

MINIMUM LOAD: Not Required.

TURN ON DELAY: 1sec max from application of DC line.

Internal Protection

OVER VOLTAGE PROTECTION: 125% ±5% of nominal. OVP shutdown is latched until the input line is removed for 30 seconds and then reapplied. OVP sensing is done at the output terminals.

OVER CURRENT PROTECTION: Current Limit Point: 110% to 120% of full load.

SHORT CIRCUIT CURRENT: Fold back type to 40%-80% of full rated current. Unit will recover when overload is removed.

REVERSE VOLTAGE PROTECTION: Protected to rated load with the fan running.

OVER TEMPERATURE PROTECTION: The unit automatically shuts down in the event of an over temperature condition. After cool down, power must be recycled to restart unit. Optionally, non-latchable protection is also available

Safety

SAFETY: UL1950, CSA22.2 No 950 and TUV to EN60950. CE Mark (LVD)

EMI: Conducted & Radiated: EN55022 Level A
 CE Certification is Optional



5" x 5" x 11.25"
 Up to 2000W
 DC Terminal Block
 AC Terminal Block
 Option Connector DB25



5" x 5" x 11.5"
 Up to 3000W
 Elcon lower Drawer
 Hot Plug Connector



5" x 5" x 17"
 Up to 5000W
 Elcon Top Drawer
 Hot Plug Connector



5" x 5" x 15.5"
 Up to 10kW
 DC Bus Bars
 AC Terminal Block
 Option Connector DB25



5" x 5" x 11.25"
 Up to 3000W
 DC Bus Bars
 AC Terminal Block
 Option Connector DB25